

floors



Features:

- PUZG plain bearing wheels:
- wheel body made of special grey cast iron with plain bearing
- tread made of polyurethane, molded, approx. 95° shore A, strong hub with core hole

Properties:

- high load capacity
- low abrasion, non-marking, shock-resistant
- low rolling resistance
- excellent chemical resistance, oil and grease resistance
- resistant to cutting by metal chips
- (old designation: series 4)



wheels	wheel ø mm	wheel width mm	axle hole ø mm	hub length mm	load-carrying capacity kg
PUZG-080-36-36-G15 Ident No.: 0038580	80	36	15	36	250
PUZG-100-30-36-G15 Ident No.: 0011978	100	30	15	36	250
PUZG-125-35-47-G15 Ident No.: 0011982	125	35	15	47	330
PUZG-150-40-47-G20 Ident No.: 0011987	150	40	20	47	500
PUZG-160-40-59-G20 Ident No.: 0035342	160	40	20	59	750
PUZG-200-50-52-G20 Ident No.: 0011993	200	50	20	52	1,000
PUZG-250-50-65-G25 Ident No.: 0011999	250	50	25	65	1,400
PUZG-250-60-65-G25 Ident No.: 0012010	250	60	25	65	1,400
PUZG-300-70-70-G25 Ident No.: 0012017	300	70	25	70	2,100
PUZG-300-100-100-G45 Ident No.: 0030732	300	100	45	100	2.500