

INSIDE DIAL CALIPER GAGE



- Graduation: metric 0.01mm
inch 0.0005"
- Option: sphere tip \varnothing 1.5mm/0.060"
- Packed in aluminum box or plastic box

Code	Range	Arm length	Tip height	Tip radius
2222-15	5-15mm	20mm	1.5mm	0.3mm
2222-20	10-20mm	25mm	3.0mm	0.3mm
2222-30	20-30mm	30mm	6.5mm	0.5mm
2222-40	30-40mm	30mm	9.0mm	0.5mm
2222-50	40-50mm	30mm	9.0mm	0.5mm
Code	Range	Arm length	Tip height	Tip radius
2222-25	5-25mm	35mm	1.5mm	0.3mm
2222-301	10-30mm	55mm	3.5mm	0.5mm
2222-401	20-40mm	80mm	6.5mm	0.5mm
2222-501	30-50mm	80mm	8.5mm	0.5mm
2222-60	40-60mm	80mm	8.5mm	0.5mm
Code	Range	Arm length	Tip height	Tip radius
2222-E06	0.2-0.6"	0.787"	0.059"	0.012"
2222-E08	0.4-0.8"	0.984"	0.118"	0.012"
2222-E12	0.8-1.2"	1.181"	0.256"	0.02"
2222-E16	1.2-1.6"	1.181"	0.354"	0.02"
2222-E20	1.6-2.0"	1.181"	0.354"	0.02"
Code	Range	Arm length	Tip height	Tip radius
2222-E10	0.2-1.0"	1.378"	0.059"	0.012"
2222-E121	0.4-1.2"	2.165"	0.138"	0.02"
2222-E161	0.8-1.6"	3.150"	0.256"	0.02"
2222-E201	1.2-2.0"	3.150"	0.335"	0.02"
2222-E24	1.6-2.4"	3.150"	0.335"	0.02"

OUTSIDE DIAL CALIPER GAGE



- Graduation: metric 0.01mm
inch 0.0005"
- Option: sphere tip $\varnothing 1.5\text{mm}/0.060\text{"}$
- Packed in aluminum box or plastic box

Code	Range	Arm length	Tip height	Tip radius
2333-10	0-10mm	40mm	8mm	0.5mm
2333-20	10-20mm	40mm	8mm	0.5mm
2333-30	20-30mm	40mm	8mm	0.5mm
2333-40	30-40mm	40mm	8mm	0.5mm
2333-50	40-50mm	40mm	8mm	0.5mm
Code	Range	Arm length	Tip height	Tip radius
2333-201	0-20mm	80mm	25mm	0.75mm
2333-301	10-30mm	80mm	25mm	0.75mm
2333-401	20-40mm	80mm	25mm	0.75mm
2333-501	30-50mm	80mm	25mm	0.75mm
2333-601	40-60mm	80mm	25mm	0.75mm
Code	Range	Arm length	Tip height	Tip radius
2333-E04	0-0.4"	1.575"	0.315"	0.02"
2333-E08	0.4-0.8"	1.575"	0.315"	0.02"
2333-E12	0.8-1.2"	1.575"	0.315"	0.02"
2333-E16	1.2-1.6"	1.575"	0.315"	0.02"
2333-E20	1.6-2.0"	1.575"	0.315"	0.02"
Code	Range	Arm length	Tip height	Tip radius
2333-E081	0-0.8"	3.150"	0.984"	0.03"
2333-E121	0.4-1.2"	3.150"	0.984"	0.03"
2333-E161	0.8-1.6"	3.150"	0.984"	0.03"
2333-E201	1.2-2.0"	3.150"	0.984"	0.03"
2333-E24	1.6-2.4"	3.150"	0.984"	0.03"

INSIDE DIAL CALIPER GAGE



Code	Range	Arm length	Tip length x diameter
2321-35	15-35mm	50mm	3x3mm
2321-55	35-55mm	80mm	6x3mm
2321-75	55-75mm	90mm	8x3mm
2321-95	75-95mm	100mm	8x3.2mm
2321-115	95-115mm	150mm	10x3.2mm
2321-135	115-135mm	150mm	10x3.2mm
Code	Range	Arm length	Tip length x diameter
2321-14	0.6-1.4"	1.9"	0.118x0.118"
2321-22	1.4-2.2"	3.1"	0.236x0.118"
2321-30	2.2-3.0"	3.1"	0.315x0.118"
2321-38	3.0-3.8"	3.9"	0.315x0.118"

- Graduation:
 - metric 0.01mm
 - inch 0.0005"
- Pin tips
- Packed in wooden box or plastic box

OUTSIDE DIAL CALIPER GAGE



Code	Range	Arm length	Tip length x diameter
2332-20	0-20mm	60mm	6x3mm
2332-40	20-40mm	60mm	6x3mm
2332-60	40-60mm	55mm	6x3mm
2332-80	60-80mm	55mm	6x3mm
2332-100	80-100mm	55mm	6x3mm
Code	Range	Arm length	Tip length x diameter
2332-08	0-0.8"	2.3"	0.236x0.118"
2332-16	0.8-1.6"	2.3"	0.236x0.118"
2332-24	1.6-2.4"	2.1"	0.236x0.118"
2332-32	2.4-3.2"	2.1"	0.236x0.118"
2332-41	3.2-4.0"	2.1"	0.236x0.118"

- Graduation:
 - metric 0.01mm
 - inch 0.0005"
- Pin tips
- Packed in wooden box or plastic box

ELECTRONIC DIGITAL INSIDE CALIPER GAGE

- Resolution: 0.01mm/0.0005"
- Option: sphere tip Ø1.5mm/0.060"
- Rotary display in digit and analog
- RS232 output port, automatic power off
- Functions: data set, ABS/INC, mm/inch, max/min, data holding, tolerance measurement
- With spare battery
- Packed in aluminum box or plastic box



Code	Range	Arm length	Tip height	Tip radius
2121-15	5-15mm/0.2-0.6"	20mm/0.79"	1.5mm/0.06"	0.3mm/0.01"
2121-20	10-20mm/0.4-0.8"	25mm/0.98"	3.0mm/0.12"	0.3mm/0.01"
2121-30	20-30mm/0.8-1.2"	30mm/1.18"	6.5mm/0.26"	0.5mm/0.02"
2121-40	30-40mm/1.2-1.6"	30mm/1.18"	9.0mm/0.35"	0.5mm/0.02"
2121-50	40-50mm/1.6-2.0"	30mm/1.18"	9.0mm/0.35"	0.5mm/0.02"
Code	Range	Arm length	Tip height	Tip radius
2121-25	5-25mm/0.2-1.0"	35mm/1.38"	2.0mm/0.08"	0.3mm/0.01"
2121-31	10-30mm/0.4-1.2"	55mm/2.17"	5.5mm/0.22"	0.5mm/0.02"
2121-41	20-40mm/0.8-1.6"	80mm/3.15"	6.5mm/0.26"	0.5mm/0.02"
2121-51	30-50mm/1.2-2.0"	80mm/3.15"	8.5mm/0.33"	0.5mm/0.02"
2121-61	40-60mm/1.6-2.4"	80mm/3.15"	8.5mm/0.33"	0.5mm/0.02"

ELECTRONIC DIGITAL OUTSIDE CALIPER GAGE

- Resolution: 0.01mm/0.0005"
- Option: sphere tip Ø1.5mm/0.060"
- Rotary display in digit and analog
- RS232 output port, automatic power off
- Functions: data set, ABS/INC, mm/inch, max/min, data holding, tolerance measurement
- With spare battery
- Packed in aluminum box or plastic box



Code	Range	Arm length	Tip height	Tip radius
2131-10	0-10mm/0-0.4"	40mm/1.57"	8mm/0.31"	0.5mm/0.02"
2131-20	10-20mm/0.4-0.8"	40mm/1.57"	8mm/0.31"	0.5mm/0.02"
2131-30	20-30mm/0.8-1.2"	40mm/1.57"	8mm/0.31"	0.5mm/0.02"
2131-40	30-40mm/1.2-1.6"	40mm/1.57"	8mm/0.31"	0.5mm/0.02"
2131-50	40-50mm/1.6-2.0"	40mm/1.57"	8mm/0.31"	0.5mm/0.02"
Code	Range	Arm length	Tip height	Tip radius
2131-21	0-20mm/0-0.8"	80mm/3.15"	25mm/0.98"	0.75mm/0.03"
2131-31	10-30mm/0.4-1.2"	80mm/3.15"	25mm/0.98"	0.75mm/0.03"
2131-41	20-40mm/0.8-1.6"	80mm/3.15"	25mm/0.98"	0.75mm/0.03"
2131-51	30-50mm/1.2-2.0"	80mm/3.15"	25mm/0.98"	0.75mm/0.03"
2131-61	40-60mm/1.6-2.4"	80mm/3.15"	25mm/0.98"	0.75mm/0.03"